## **MATERIAL SAFETY DATA SHEET**

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

	IDENTITY AND [	DISTRIBUTO	OR'S INFORMATION	N			
NFPA Rating: Health-2; Flammability-2; Reactivity-0; Special-0 HMIS Rating: Health-2; Flammability-2; Reactivity-0; Personal Protection-B							
Manufactured For: Triple S DOT Hazard Classification: ORM-D							
Address:	2 Executive Park Dr.	lder	Identity (trade name as used on label):				
	Billerica, MA 01862		SSS Dust Mop Treatment #05010				
			ISDS Number: A00810 Revision- 9				
			Date Prepared: 04/12/93 Prepared By: ES				
			nformation Calls: 978-667-7900				
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION							
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES  CAS Number  SARA OSHA PEL ACGIH Carcinogen							
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)  PETROLEUM DISTILLATE			0050 44 0	III LIST	(ppm)	TLV (ppm)	Ref. Source **
ISOBUTANE			8052-41-3	No	500	100	d
PETROLEUM DISTILLATE			75-28-5	No	800	800	d
PETROLEUM DISTILLATE			64742-54-7	No	5mg/M3	5mg/M3	d
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.910							
			/apor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A Evaporation Rate ( = 1): N/E				
Appearance and Odor: White, creamy spray with pine fragrance.  SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
FLAMMABILITY as per USA FL			nition Temperature		ability Limits	in Air by % i	n Volumo:
(aerosols) NON-FLAMMABLE		Auto igi	N/E		iability Liffits .: N/E	% UEL	
FLASH POINT AND METHOD USE		FXT					
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.  EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT							
OCCUR							
Incompatibility (Mat. to avoid): Strong oxidizers.  Conditions to Avoid: Open flame, welding arcs, heat, sparks.							
Hazardous Decomposition Products: CO, CO2.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS:							
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, weakness, fatigue, anesthetic effects and possible							
unconsciousness.							
Eye Contact: Irritation, Defatting, redness							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea, vomitting, diarrhea, central nervous system depression.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause skin burns, asthma like symptoms,							
aspiration hazard.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Aspiration hazard. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.							
Protective Gloves: Latex, if skin easily irritated.  Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE  Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal							
regulations. DO NOT FLUSH TO SEWER.							
,		haria praes:::	ro through named	0 0000 =	o dianasal La	zord	
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.  Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.							
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Remove ignition sources. Avoid prolonged breathing of spray mist							
prolonged breathing of spray mist.							